





系列码	类型	材 质	类 型
CAZ	标准型	轴承钢 SUJ2	轴承钢型

带保持器止推滚针



止推圈



止推圈在交货时会有一些变化，
以同心圆的方式施加最低200N轴
向负载即可使之平整。

精度 GB/T307 0级

型式	带保持器止推滚针								止推圈×2						容许转速	重量	基本动态	基本静态
●系列码	d	公差	D	公差	B	公差	F	F ₁	d ₁	公差	D ₁	公差	B ₁	公差	rpm (参考)	(g) (参考)	额定负载 Ca kN	额定负载 Coa kN
CAZ0414	4		14	-0.095 -0.365			13	5	4		14	-0.032 -0.302			5200	2.7	4.4	8.0
CAZ0515	5	+0.140 +0.020	15				14	6	5	+0.200 +0.020	15				5200	2.8	4.75	9.2
CAZ0619	6		19	-0.110 -0.440			18	7	6		19				4700	5	6.8	15.5
CAZ0821	8	+0.175 +0.025	21				20	9	8	+0.245 +0.025	21				4500	6	7.8	19.4
CAZ1024	10		24				23	12	10		24	-0.040 -0.370			4200	9	9.2	25.5
CAZ1226	12		26	-0.110 -0.440	2	0 -0.01	25	14	12		26		1	+0.05 -0.05	3700	9	9.9	29.0
CAZ1528	15	+0.212 +0.032	28				27	17	15	+0.302 +0.032	28				3200	10	11.3	36.0
CAZ1730	17		30				29	19	17		30				3000	12	11.9	39.5
CAZ2035	20		35	-0.120 -0.510			34	22	20		35				2500	15	13.1	46.5
CAZ2542	25	+0.250 +0.004	42	-0.130 -0.520			41	29	25	+0.370 +0.040	42	-0.050 -0.440			2100	21	14.7	58.0
CAZ3047	30		47				46	34	30		47				1800	24	16.3	70.0

选型举例
Sample Order

系列码
CAZ0414
CAZ0619